




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A23G 9/14</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/26800</b> (43) International Publication Date: <b>31 July 1997 (31.07.97)</b>
<p>(21) International Application Number: <b>PCT/DK97/00028</b></p> <p>(22) International Filing Date: <b>22 January 1997 (22.01.97)</b></p> <p>(30) Priority Data: <b>0082/96</b>                      <b>22 January 1996 (22.01.96)</b>                      <b>DK</b></p> <p>(71) Applicant (for all designated States except US): <b>TETRA PAK HOYER A/S [DK/DK]; Søren Nymarks Vej 13, DK-8270 Højbjerg (DK).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): <b>GONON, Peter [DK/DK]; Lauge Kochs Vej 8, DK-8200 Århus N (DK).</b></p> <p>(74) Agent: <b>K. SKØTT-JENSEN, PATENTINGENIØRER A/S; Lemmingvej 225, DK-8361 Hasselager (DK).</b></p>	<p>(81) Designated States: <b>AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TT, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</b></p> <p><b>Published</b> <i>With international search report.</i> <i>In English translation (filed in Danish).</i></p>	

(54) Title: METHOD AND APPARATUS FOR PRODUCTION OF ICE-CREAM



## (57) Abstract

In the production of ice-cream products which are continuously extruded after passage of a flowthrough freezer, it would be ideal if the ice-cream could hereby be brought down to a discharge temperature of -12 to -25 degrees centigrade, as the products could then be brought directly to final storing. So far, however, this has not been practically possible, since the use of conventional production technique with associated throughflow freezers creates fatal problems with respect to an unacceptable compaction of the air filled ice-cream and the heat development by the conveying and scraping effect of the conveyor worm in the throughflow freezer. The invention provides for a solution of both of these problems, partly by ensuring an acceptable air filling in using an adjustable resistance at the discharge side of the freezer, and partly in that this freezer itself is provided with a conveyor worm which, for effecting a very low scraping speed, has a very high pitch and is driven with an unusually low speed of rotation.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Benin	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TC	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## C L A I M S :

1. A method of effecting continuous production of an ice-cream substance, by which the previously cooled, air holding substance is passed through a continuous freezer for further cooling down to  $-12 - -15^{\circ}\text{C}$  for subsequent extrusion, the substance being supplied to the freezer through a pipe of a first pipe dimension, characterized in that the ice-cream, downstream of the freezer, is passed through a pipe area which is narrower than said first pipe dimension, preferably in such a controllable manner that it is possible to adjust the associated flow resistance for the ice-cream substance, this resistance being adjusted to ensure a high overrun of the extruded substance.

2. A system for carrying out the method according to claim 2, comprising a continuous freezer of the screw worm conveying and scraping type with an infeed pipe of a first pipe dimension and a discharge pipe connected to an extrusion outlet for the frozen ice-cream, characterized in that the discharge pipe exhibits a constriction to a dimension smaller than said first pipe dimension, this constriction preferably being controllable for enabling its flowing resistance towards the ice-cream to be adjusted.

3. A system according to claim 2, characterized in that the said constriction is a controllable unit for mechanically adjusting the cross sectional area of the constriction.

4. A system according to claim 2, characterized in that the constriction is constituted by a pipe portion provided or connected with means for adjustably heating the pipe portion.

5. A system according to claim 2, in which the continuous freezer is made as a cylinder with a driven screw rotor for forcing the ice-cream through and out of the cylinder and for scraping off solid ice formations on the inside of the cylinder, characterized in that the screw rotor is connected with means for rotating it with very low speed, viz. in the range of 5-20 r.p.m., and that the pitch of the

conveying and scraping worm of the screw rotor is very large, viz. 1-2 times the outer diameter of the worm.

6. A system according to claim 5, characterized in that at the outside of the continuous freezer there is an operation temperature of  $-40$  to  $-100^{\circ}\text{C}$ .

1/1




Fig.1




Fig.2

1  
INTERNATIONAL SEARCH REPORT

International application No.  
PCT/DK 97/00028

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC6: A23G 9/14

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DIALOG

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0401512 A1 (HMF KRAMPE & CO. GMBH ET AL), 12 December 1990 (12.12.90), column 9, line 26 - line 36, figure 3, abstract	1-6
	--	
A	DE 3837604 A1 (LUMEN GMBH NAHRMITTEL- UND MASCHINENFABRIK), 10 May 1990 (10.05.90), figure 1, abstract	1-6
	-----	

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*B\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

\*Z\* document member of the same patent family

Date of the actual completion of the international search

25 April 1997

Date of mailing of the international search report

08 -05- 1997

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Wiva Asplund  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

02/04/97

International application No.  
PCT/DK 97/00028

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0401512 A1	12/12/90	SE 0401512 T3	
		AT 116528 T	15/01/95
		AU 5670190 A	07/01/91
		DE 3918268 C,R	26/07/90
		ES 2066900 T	16/03/95
		WO 9014775 A	13/12/90
DE 3837604 A1	10/05/90	DE 5890336 A	04/03/93
		EP 0441819 A,B	21/08/91
		SE 0441819 T3	
		US 5201861 A	13/04/93
		WO 9004927 A	17/05/90

